



Audio

Frequency response 55Hz – 20kHz

Drivers Custom full-range 75mm neodymium drivers

Amplifier 20W Class AB

Cabinet type Tuned bass reflex

Enhancements Bass, treble, loudness, 3D audio

Digital to analogue Σ - Δ 24-bit stereo DAC

Connectivity

App controlled With Ruark Link app (iOS & Android)

Multi-room Compatible with R2 mk3 & R7 mk3

Bluetooth V4.0, SBC, AAC, A2DP, aptX

Wi-Fi 802.11b/g; WEP, WPA & WPA2 security

Ethernet RJ45

Music services Spotify Connect, Amazon Music, Deezer, Tidal

Internet radio

Media Compatible with UPnP™ DLNA media servers, supports MP3, WMA, AAC, FLAC & WAV

Aux in Stereo 3.5mm jack

Optical in 3.5mm optical jack

USB 2.0 playback, 5V 1A (5W) charge port

Features

Landscape or portrait mode

Selectable stereo mode Stereo / mono / left / right

Stand Anodised aluminium

Wall mountable 2 x UNC 1/4in threads at 59mm centres on back panel

General Specifications

Finishes Rich walnut veneer or soft grey with grey woven grille fabric

Box contains MRx speaker, mains power adapter, 3.5mm optical adapter, stand, user guide

Power adapter 100-240VAC 50-60Hz input

14VDC 2.0A output, 1.8m cable, 2.1 x 5.5mm DC plug

Product dimensions (including stand)

In landscape

W300 x H180 x D180mm max (11.8 x 7.1 x 7.1in)

In portrait

W160 x H320 x D180mm max (6.3 x 12.6 x 7.1in)

Product weight 3.4kg (7.5lbs)

Inner carton dimensions

W375 x H265 x D235mm (14.8 x 10.4 x 9.3in)

Packaged weight (excl. outer carton)

3.7kg (8.2lbs)

Outer carton dimensions

W495 x H290 x D400mm (19.5 x 11.4 x 15.8in)

Outer carton weight

9.7kg

Outer carton quantity 2

