



## Audio

### Frequency response

40Hz - 22kHz (typical in-room)

### Tweeter

27mm Ruark silk dome

### Woofers

165mm/6.55" Ruark NS+, long-throw driver, treated fibre cone, 35mm 2-layer copper voice coil, Strontium ferrite motor

### Cabinet type

Dual-flared tuned bass-reflex with decoupled baffle

### Cabinet volume

14.5 litres

### Tuning frequency

42Hz

### Nominal impedance

6Ω (min 3.8Ω @ 5kHz)

### Crossover frequency

2.2kHz

### Crossover type

Optimised 2nd order, premium audio film capacitors, low-loss inductors

### Sensitivity (2.83v @ 1m)

87dB

### Amplifier requirements

75-300W

### Connection type

Dual gold-plated 4mm multi-way binding posts for single-wire or bi-wire connection. Compatible with banana plug, spade terminal or bare wire.

### Grille

Removable magnetic frame with acoustically transparent fabric

### Placement

Floorstanding

### Product dimensions (single speaker)

H850 x W210 x D250mm

### Product weight (single speaker)

17.6kg

### Carton dimensions (single speaker)

H975 x W325 x D395mm

### Packaged weight (single speaker)

20.5kg

## In the box

Talisman-R (single)  
Optional floor spikes  
Quick start guide

## General specifications

### Standard finishes

Fused Walnut veneer baffle with Charcoal cabinet & fabric grille

Satin Charcoal lacquer baffle with Charcoal cabinet & fabric grille

