

# GRAVIS

---

## *Sonus faber*

Class & Power



# GRAVIS V

## LOUDSPEAKER TYPE:

Closed box loading, single driver, active subwoofer

## WOOFER:

1 x 320mm (12") double coil 4+4ohm, very long throw, sandwich honeycomb cone, wide rubber surround

**AMPLIFIER TYPE:** High performance, class AB amplifier

**POWER AMPLIFIER (MAX):** 850 W

**FREQUENCY RESPONSE:** 20 Hz (@ - 6dB, acoustic Linkwitz 4th order roll-on, EQ1 setting) to Fc (user continuously adjustable)

## MAINS INPUT VOLTAGE:

Selectable, 120Vac - 60Hz or 230 Vac - 50 Hz

## FUSE:

T12A H 250V (for 230 Vac - 50Hz) T6.3A H 250V (for 110 Vac - 60Hz)

**CONTROLS:** Direct access Master volume; App control featuring: volume, continuously adjustable crossover frequency (40 to 150Hz), filtering slope 24dB/oct; continuously adjustable signal phase; parametric EQ (4 presets available), Delay (1 to 20 ms); auto eq; auto power on/off switch

**ADDITIONAL FEATURES:** Wireless connection (receiver included and transmitter unit available separately)

## AUDIO SIGNAL INPUTS:

2x Line level, left and right RCA phono plugs (unbalanced)  
2x Line Level, left and right XLR plugs (balanced)  
1x High level, Neutrik 4-pole Speakon®

**DATA CONNECTION:** Ethernet (external control) and USB (for firmware update only)

**POWER CONSUMPTION:** 0.5 W (Stand-by) 1200W (Peak)

## FINISHES:

Black leather Top finish: Piano Black, Wengè, Red

**DIMENSIONS (HXWXD):** 455x448,5x448,5 mm

**WEIGHT (KG):** 32

## SUPPLIED ACCESSORIES:

User manual AC Power cord Neutrik Speakon® 10m amplifier to sub interconnection cable

# GRAVIS VI

## LOUDSPEAKER TYPE:

Closed box loading, two-driver, active subwoofer

## WOOFER:

2 x 320mm (12") double coil 4+4ohm, very long throw, sandwich honeycomb cone, wide rubber surround woofer

**AMPLIFIER TYPE:** High performance, class AB amplifier

**POWER AMPLIFIER (MAX):** 1.800 W

**FREQUENCY RESPONSE:** 18 Hz (@ - 6dB, acoustic Linkwitz 4th order roll-on, EQ1 setting) to Fc (user continuously adjustable)

## MAINS INPUT VOLTAGE:

Selectable, 120Vac - 60Hz or 230 Vac - 50 Hz

## FUSE:

T12A H 250V (for 230 Vac - 60Hz) T6.3A H 250V (for 110 Vac - 50Hz)

**CONTROLS:** Direct access Master volume; App control featuring: volume, continuously adjustable crossover frequency (40 to 150Hz), filtering slope 24dB/oct; continuously adjustable signal phase; parametric EQ (4 presets available), Delay (1 to 20 ms); auto eq; auto power on/off switch

**ADDITIONAL FEATURES:** Wireless connection (receiver included and transmitter unit available separately)

## AUDIO SIGNAL INPUTS:

2x Line level, left and right/LFE RCA phono plugs (unbalanced)  
2x Line Level, left and right/LFE XLR plugs (balanced)  
1x High level, Neutrik 4-pole Speakon®

**POWER CONSUMPTION:** 0.5 W (Stand-by) 1800W (Peak)

## FINISHES:

Black leather Top finish: Piano Black, Wengè, Red

**DIMENSIONS (HXWXD):** 616x448,5x585,5 mm

**WEIGHT (KG):** 52

## SUPPLIED ACCESSORIES:

User manual AC Power cord Neutrik Speakon® 10m amplifier to sub interconnection cable